# AI DON **CORPORATION**

### MATERIAL SAFETY DATA SHEET

221 Rochester Street Avon, New York 14414-9409

MSDS No.: PP0600 Effective Date: January 1, 2007

## (585) 226-6177

SECTIO	N I NAME	2	4 HOUF	REME	RGENCY	ASSIS	TAN	CE
Product	Potassium Hydroxide, 0.1 Molar Solution (0.1N)			CI	HEMTREC		-	٦
Chemical Synonyms	Potassium Hydroxide, Water Solution		800-424-930		0-424-9300	Health	3	- 1
	<u> </u>	.	$\langle \ \ \ \ \ \rangle$	Day	585-226-6177	Fire	0	<u>'</u>
Formula	Mixture.		NFP	Α		Reactiv	ity 1	
Unit Size	up to 3.785 Lt.		HAZARE				IIS *	_
C.A.S. No.	Mixture.		MINIMAL 0	SLIGHT 1	MODERATE 2	SERIOUS 3	SEVER	ŧΕ

SECTION II INGREDIENTS OF MIXTURES							
Principal Component(s)	%	TLV Units					
Potassium hydroxide: CAS No. 1310-58-3	0.57%	STEL: C 2 mg/m <sup>3</sup>					
Water: CAS No. 7732-18-5	99.43%						
DANGER! CORROSIVE!							
HARMFUL IF SWALLOWED. CAUSES BURNS.							

<b>SECTION III</b>	PHYSICAL DATA				
Melting Point (°F)	Freezes @ ~ 0°C (32°F)	Specific Gravity (H <sub>2</sub> O = 1)	~ 1.1		
Boiling Point (°F)	~ 100°C (212°F)	Percent Volatile by Volume (%)	99.43%		
Vapor Pressure (mm Hg)	14 (water)	Evaporation Rate ( Water =1)	< 1		
Vapor Density (Air=1)	0.7 (water)				
Solubility in Water	Complete.				
Appearance & Odor	Clear, colorless liquid; no odor.	_	_		

SECTION	IIV FIRE A	FIRE AND EXPLOSION HAZARD DATA						
Flash Point (Method Used)	Non-flammable.	Flammable Limits in Air % by Volume N/A	Lower	Upper				
Extinguisher Media	Water spray, foam, ca	rbon dioxide, dry chemical.						

### SPECIAL FIREFIGHTING **PROCEDURES**

In fire conditions, wear a NIOSH/MSHA-approved self-contained breathing apparatus and full protective clothing. Must include complete eye protection. Flood with water, using care not to splatter or splash this material.

(2004 EMERGENCY RESPONSE GUIDEBOOK, RSPA P 5800.9, GUIDE PAGE NO. 154)

**UNUSUAL FIRE AND EXPLOSION HAZARDS** 

> In fire conditions, water may evaporate from this material causing hazardous decomposition materials to be formed as dust or fume. Contact with some metals can generate hydrogen gas. A severe eye hazard; solid or concentrated solution destroys tissue on contact.

Potassium hydroxide, solution, 8, UN1814, PG II, Ltd Qtv ≤1 Lt. D.O.T.

#### SECTION V **HEALTH HAZARD DATA Threshold Limited Value** None established for this mixture. ACGIH 2001. Toxicity data: RTECS # TT2100000 LD50: oral rat: 273 mg/kg. For Potassium hydroxide. Harmful if swallowed, inhaled or absorbed through skin. Material is extremely **Effects of Overexposure** destructive to tissues of the mucous membranes, upper respiratory tract, skin and eyes. Inhalation may be fatal as a result of spasm, inflammation and edema of the larynx and bronchi, chemical pneumonitis and pulmonary edema. Symptoms of exposure may include burning sensation, coughing, wheezing, laryngitis, shortness of breath, headache, nausea and vomiting. Target organs: None known. **Emergency and** INGESTION: Call physician or Poison Control Center immediately. Induce **First Aid Procedures** vomiting only if advised by appropriate medical personnel. Never give anything by mouth to an unconscious person. EYES: Check for and remove contact lenses. Flush thoroughly with water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get immediate medical attention. SKIN: Remove contaminated clothing. Flush thoroughly with mild soap and water. If irritation occurs, get medical attention. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. **SECTION VI** REACTIVITY DATA Conditions to Avoid Unstable Stability Excessive temperature and heat to cause evaporation. Stable Χ Incompatibility Acids, aluminum, halogens, nitro compounds, organic materials, acid chlorides, (Materials to Avoid) acid anhydrides, magnesium, copper, tin and zinc. **Hazardous** Hydrogen gas. Generates flammable and/or explosive hydrogen gas in **Decomposition Products** contact with metals. **Hazardous Polymerization Conditions to Avoid May Occur** Will Not Occur Not applicable. SPILL OR LEAK PROCEDURES SECTION VII

Steps to be taken in case material is released or spilled

Wearing protective clothing, carefully absorb spilled material with an inert dry material, sweep up and place in a suitable container for proper disposal. Flush spill area with soap and water.

PP0600

**Waste Disposal Method** 

Discharge, treatment, or disposal may be subject to Federal, State or Local laws. These disposal guidelines are intended for the disposal of catalog-size quantities only.

Contract with a licensed waste disposal agency.

					•			
SECTION V	/III	SP	<b>ECIAL PROT</b>	EC	TION II	NFOR	MATION	
Respiration Protect (Specify Type)			d in normal laborator ood or wear a NIOSI				nditions prevail, work in mask or respirator.	
Ventilation	Local Ex	haust	Recommende	d.	Special	No.		
ventilation	Mechanical (General)		Recommended.		Other	No.		
Protective Gloves		R	ubber.	Eye Protection		ection	Chemical safety goggles or face shield where appropriate.	
Other Protective Equipment	Go	Goggles, lab coat, apron, ventilation hood, proper gloves, eye wash station.						
<b>SECTION I</b>	Χ	SP	<b>ECIAL PREC</b>	ΑU	TIONS			
Precautions to be Taken in Handling & Storing		310	Store in a cool, well-ventilated place. Separate from acids, metals, explosives,					

Keep container tightly closed when not in use.

organic peroxides and easily ignitable materials. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.

Other Precautions

Read label on container before using. Do not wear contact lenses when working with chemicals.

Product is deliquescent and absorbs water and Carbon dioxide from air. Potassium hydroxide and trichloroethylene are especially hazardous since they react to form spontaneously flammable dichloroacetylene. Remove and wash contaminated clothing.

Date 01/01/07 Approved

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure prohealth of employees. \* Hazardous Materials Industrial Standards. Printed on recycled paper.